

3M™ Extreme Sealing Tape 4412N

Extremely
Fast
Clean
Easy



From rain gutters to flashing and vents
a sure winner over traditional sealants

3M™ Extreme Sealing Tape 4412N – rolls on fast and looks good

- Sticks on contact to many metals and plastics without drying time, dripping, oozing, and clean-up
- No sticky mess on hands
- Conforms over contours, edges, rivets and screw heads for a water tight seal
- No caulking guns to buy, clean and store, and no empty cartridges for disposal
- Paintable to color blend with the adjoining surfaces
- Neat and precise looking for aesthetics

Over time even more extreme advantages become obvious

- Holds securely through sun, rain, snow, temperature extremes, and abrasion
- Stays flexible to compensate for vibration and thermal expansion/contraction
- No cracking and crumbling

Seaming and sealing ideas

- Parapet walls
- Trailer home roofs
- Metal buildings
- Vent stacks and vent windows
- Gutters and downspouts
- Skylights
- Patching
- Trailer and RV roofs
- Metal enclosures

Distributed by

Hisco
Fast Friendly Service

1-877-447-2650
www.hiscoinc.com

3M

3M™ Extreme Sealing Tape 4412N - rolls on fast and tight and stays that way



5 Simply clean with a solution of water and isopropyl alcohol and wipe dry.



6 Sticks on contact exactly where you roll it on. No drips and oozing. No waiting.



7 Roll down with a soft roller to conform over contours, seam edges, rivets, or screw heads.



8 Peel off the protective release liner.



9 Burnish once more to optimize adherence and conformance to uneven surfaces.



10 From rooftops to underground cable enclosures - durable sealing through heat, cold, and weather without cracking or edge lifting.

11

Product Information

Product/Color	Backing/Adhesive	Tape Thickness (mm)	Tensile Strength (N/cm)	90° Peel Strength (N/cm)				Widths (mm)	Comments
				Aluminum	Steel	PVC	ABS		
4412N Translucent White	Ionomer film/ Pressure sensitive acrylic	2.0	21	9 (18*)	7 (17*)	9 (20**)	2 (20**)	25, 50, 60, 75	Resists yellowing, cracking, and edge lifting

* With 3M™ Adhesion Promoter 111 ** With 3M™ Primer 94

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. **Warranty, Limited Remedy, and Disclaimer:** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR CONDITION. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Available from Hisco

UPC	Size	Case Qty
00-051115-31985-3	50 mm x 10 m	5 Rolls



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 . 877-369-2923 (Fax)
www.3M.com/vhb

3M is a trademark of 3M Company.
© 3M 2010

Distributed by



1-877-447-2650
www.hiscoinc.com